



LUMA 12 / 14 / 18 SLIM

FLUSH MOUNT CEILING

location: **DAMP**

SPECIFICATIONS:

DESCRIPTION

Flush-mounted round ceiling luminaires, featuring handcrafted glass. "Slim" design features a low profile pan specifically for CFL lamps. Three sizes available.

LAMPING

Standard: 60W A19 120V incandescent, suitable for dimming, not included.
CFL: 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.
GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.
LED: 10W GU24 LED Lamp 120V, dimmable, included.
Consult factory for other CFL configurations., *CFL lamps not included.*

DIFFUSER

Handcrafted glass diffuser is available in Opal Glossy/Clear decor.
Luma 12 Slim #9095XX: 11.875" Dia. x 3.75" H
Luma 14 Slim #9096XX: 14.375" Dia. x 4.375" H
Luma 18 Slim #9097XX: 17.25" Dia. x 4.75" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



LUMA SLIM CEILING SHOWN IN OPAL GLOSSY/CLEAR

Luma 12 Slim: #9095




FIXTURE	DECOR	LAMP OPTIONS	OPTIONS
1CS 11.875" Dia.	909539 Opal Glossy/Clear	(blank) 1x 60W A19 Incan D1 1x 13W Quad 120V GU24 1x 13W GU24 120V LED 1x 10W LED 120V, dimmable	LW Low Wattage labeling

Luma 14 Slim: #9096



FIXTURE	DECOR	LAMP OPTIONS	OPTIONS
2CS 14.375" Dia.	909639 Opal Glossy/Clear	(blank) 2x 60W A19 Incan D2 2x 13W Quad 120V GU24 2x 13W GU24 120V LED 2x 10W LED 120V, dimmable	LW Low Wattage labeling

Luma 18 Slim: #9097



FIXTURE	DECOR	LAMP OPTIONS	OPTIONS
3CS 17.75" Dia.	909739 Opal Glossy/Clear	(blank) 3x 60W A19 Incan H2 2x 26W Quad 120V GU24 3x 13W GU24 120V LED 3x 10W LED 120V, dimmable	LW Low Wattage labeling

Ex. 1CS-909539

Luma 12 Slim Ceiling w/ Opal Glossy/Clear Glass

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

Project Information:

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.