



TAMBURO 16V2

SEMI-FLUSH MOUNT CEILING



SPECIFICATIONS:

DESCRIPTION

Semi-flush mounted ceiling luminaires, featuring handcrafted glass. "Near Ceiling" design creates soft ceiling glow.

LAMPING

Standard: 3x60W A19 120V incandescent, suitable for dimming, not included.

CFL: Standard 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 26W max, 120V, lamp not included.

LED: 10W GU24 LED Lamp 120V, dimmable, included.

DIFFUSER

Handcrafted glass diffuser is available in various decors. 15.75" Dia. x 8" H

CONSTRUCTION

Canopy (5" dia.) is plated stamped steel. Canopy and glass retainer hardware are available in either Bronze or Satin Nickel finish.

MOUNTING


Installs directly to a 4" octagonal outlet box, centered on fixture. 90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



TAMBURO 16V2 CEILING SHOWN IN GLITTER STONE (4008GL)



4008GS
STONE GOLD FOIL



4008CS
STONE COPPER FOIL



4008SS
STONE SILVER FOIL



400800
CLEAR STONE



4008SF
SILVER FOIL



4008KR
CHALK



4008TN
TITAN



4008OK
OAK



4008CH
CHERRY



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



TAMBURO 16V2

SEMI-FLUSH MOUNT CEILING

ORDERING:

| FIXTURE | GLASS OPTIONS | LAMP OPTIONS | METAL FINISH | OPTIONS |
|----------------|--------------------------|----------------------------------|-----------------|----------------|
| 1KM 1 Lt. Flat | 4008CH Cherry | (blank) 3x 60W A19 Incan | BR Bronze | LW Low Wattage |
| | 4008KR Chalk | I3 3x 26W TBX 120V | SN Satin Nickel | labeling |
| | 4008OK Oak | R3 3x 26W TBX 277V | | |
| | 4008TN Titan | GU24 3x 26W GU24 | | |
| | 400800 Clear Stone | LED 3x 10W LED 120V, dimmable | | |
| | 4008CS Stone Copper Foil | | | |
| | 4008GL Glitter Stone | | | |
| | 4008GS Stone Gold Foil | | | |
| | 4008SF Silver Foil | | | |
| | 4008SS Stone Silver Foil | | | |

Ex. 1KM-4008OK-SN
 3 Lt. Flat Ceiling w/ Oak Glass,
 Satin Nickel Finish

Project Information:

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+