



# TAO 10

120V PENDANTS



## SPECIFICATIONS:

### DESCRIPTION

Cord-hung, cable-hung or stem-mount pendant with handcrafted glass diffuser.

### LAMPING

**Standard:** 100W A19 120V incandescent, suitable for dimming, not included.

**CFL:** 26W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

**GU24 CFL:** Self-ballasted GU24 lampholders. 26W max, 120V, lamp not included.

**LED:** 10W GU24 LED Lamp 120V, dimmable, included.

### DIFFUSER

Shade shall be handcrafted glass of various decors. 5.125" Dia. x 10.75" H

**Opening sizes:** 58mm min. (top), 119mm min. (bottom), 3x7mm holes.

### SUSPENSION

**Cord-hung:** 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Available on 1, 3 or 6 light canopies, shown on next page. Plated stamped steel construction. Bronze or Satin Nickel.

**Cable-hung:** 1x 10' aircraft-quality stainless steel cable support with 10' AWM-type cord. Jacket coordinates with metal finish. 5" Dia. dome canopy is plated stamped steel. Bronze or Satin Nickel.

**Stem-mount:** 4 connectable stem sections (3", 6", 12" and 18" lengths), 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.


### MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

### LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



TAO 10 SHOWN IN OPAL MATTE (151207) & VANILLA MATTE (1512VM)

1512RM  
RUBY MATTE

1512CM  
COBALT BLUE MATTE

1512HV  
HALVA

1512OK  
OAK

1512CH  
CHERRY

1512KR  
CHALK

1512TN  
TITAN



For ordering information, see next page

All dimensions provided are nominal.  
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



## TAO 10

120V PENDANTS


### ORDERING:

CONNECTION	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
Cord Fixture	<b>151207</b> Opal Matte	(blank) 100W A19 Incan	<b>BR</b> Bronze	<b>L</b> 15' cord
<b>1JC</b> 1 Lt. Dome	<b>1512CH</b> Cherry	<b>H1</b> 26W Quad 120V	<b>SN</b> Satin Nickel	<b>LW</b> Low wattage labeling
<b>1JT</b> 1 Lt. Flat	<b>1512CM</b> Cobalt Blue Matte	<b>Q1</b> 26W Quad 277V		
	<b>1512HV</b> Halva	<b>GU24</b> 26W GU24 120V		
Cable Fixture	<b>1512KR</b> Chalk	<b>LED</b> 10W LED 120V, dimmable		
<b>1KX</b> 1 Lt. Dome	<b>1512OK</b> Oak			
	<b>1512RM</b> Ruby Matte			
Stem Fixture	<b>1512TN</b> Titan			
<b>1TT</b> 1 Lt. Flat	<b>1512VM</b> Vanilla Matte			

**Ex. 1JC-1512OK-SN**  
Tao 10 Pendant w/ Oak Glass,  
Satin Nickel Finish


### PENDANT OPTIONS:

#### MONOPOINT PENDANT CANOPY




- Flat or Dome Canopy styles. Dome style allows adjustment without cutting cord.
- Suitable for sloped ceilings
- Cord: 10' SVT, 5" sleeve at socketholder (V Series utilizes SJT-type)
- Bronze or Satin Nickel

#### 3BB or 3JB 3 LIGHT LINEAR CANOPY




- 2x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

#### 3BC or 3JC 3 LIGHT ROUND CANOPY




- 3x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

#### 3BW or 3JW 3 LIGHT LARGE ROUND CANOPY




- 3x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

#### 3BV or 3JV 3 LIGHT BAR CANOPY




- Some offset installation possible
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve at socketholder
- Bronze or Satin Nickel

#### 6BC or 6JC 6 LIGHT ROUND CANOPY




- 6x stemhooks included
- Suitable for sloped ceilings
- Cords: 10' SVT, 5" sleeve
- Bronze or Satin Nickel

#### CABLE-HUNG PENDANT



- 1x 10' aircraft-quality stainless steel cable
- Suitable for sloped ceilings
- 1x lampholder
- 4-pin CFL options available
- Cord: 10' AWM-type provided
- Bronze or Satin Nickel

#### STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3', 1x 6', 1x 12', 1x 18"), 10' max
- Bronze or Satin Nickel

### LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

### ACCESSORIES:

#### ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

<b>T20A-SN</b> or <b>T20A-BR</b>	Adj. Section
<b>T203-SN</b> or <b>T203-BR</b>	3" Section
<b>T206-SN</b> or <b>T206-BR</b>	6" Section
<b>T212-SN</b> or <b>T212-BR</b>	12" Section
<b>T218-SN</b> or <b>T218-BR</b>	18" Section

#### LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an "L" to the end of the item number, i.e. 1JC-169707-SNL.

#### CORD SLEEVES:

If concealing the cord is desired, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

<b>T118-SN</b>	Satin Nickel
<b>T118-BR</b>	Bronze

#### STEMHOOKS:

Suspension hooks allow cord drops to be placed wherever desired. Suitable for sloped ceilings.

<b>T103BR</b>	Bronze
<b>T103SN</b>	Satin Nickel

### HOW TO ORDER A MULTILIGHT FIXTURE

To order, simply place the 3 character multilight code (*shown to the right*) as the cord fixture option:

**Example: 3BC-493007-SN**  
3 Light round, Copa Opal glass, Satin Nickel finish

### Project Information: