



SPUTNIK

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with aluminum and acrylic diffuser.

LAMPING

LED: 6W integrated lightsource, dimmable.

DIFFUSER

Shade shall be acrylics of frost decor. 2.25" Dia. x 2.5" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

STANDARD PENDANT (1XT)

Mini pendant comes complete with flat-style canopy.

METAL FINISH


Glass retainer hardware, sleeve and Quick-Connect Jack and/or canopies are finished in Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



SPUTNIK (SPUTNK)




LED 12V MINI PENDANTS:

- LED driver is located in canopy for optimal performance
- Total power of 6 watts
- 450 lumens
- Rated life: 30,000 hours
- CCT: 2800° Kelvin
- CRI: 85+
- Dimmable
- Frosted acrylic diffuser encloses LEDs

Project Information:

FIXED PENDANT OPTIONS:

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

ORDERING:

CONNECTION	GLASS OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	SPUTNK Sputnik	LED 6W LED	SN Satin Nickel
1XT Flat Canopy			

Ex. 1XT-FLOWAM-LED-SN
Flower LED Mini Pendant, Amber Acrylics,
Satin Nickel Finish

For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14